

iM2-UART-4P

M.2 B Key & M Key card supports four RS-232/422/485 Port, RoHs



Features

- » M.2 B Key + M Key card supports four RS-232/422/485 Port
- » 128 bytes transmit/receive FIFO
- » High-speed 16C550/16C650/16C750/16C850 compatible UARTs
- » Baud rate supports 115.2K, max. up to 1.5M

Specifications

Form Factor	
Form Factor	M.2 B Key + M Key card
System	
Chipset	Fintek F81504 (PCI Express Bridge to Quad Serial Port), Fintek F81439 (Buffer/Transceiver Series)
Physical Characteristics	
Dimensions (LxWxH) (mm)	22mm x 80mm
Net Weight	GW: 100g / NW: 50g
I/O Interface	
I/O Interface	4 x Internal RS-232/422/485 : pin header (2x5 pin, P=2.0)
Environment	
Operating Temperature	0°C ~ 60°C
Storage Temperature	-30°C ~ 70°C
Humidity	5% ~ 95%, non-condensing
Certifications	
Safety & EMC	CE/FCC compliant
Card Slot Interface	
M.2	M.2 B/M key 3042 (PCIe gen3 x1 signal)

Ordering Information

iM2-UART-4P-R10	M.2 B Key&M Key card supports four RS-232/422/485 Port, RoHs
-----------------	--

Packing List

1 x iM2-UART-4P card	2 x D-SUB9 male cable
1 x QIG (Quick Installation Guide)	