

IOVU-430S

4.3" TFT WQVGA LCD with resistive touchscreen



Features

- » 4.3" TFT WQVGA LCD with resistive touchscreen
- » Samsung S3C2416 400MHz CPU
- » Powered by Windows® CE 6.0
- » Built-in Ethernet LAN and optional Wi-Fi
- » Built-in CAN-bus 2.0b and GPIO
- » Built-in RS-232/422/485 Port
- » Support .Net Frame Work V3.5

Specifications

System	CPU
On-board Memory	128MB
Memory Ext.	128 MB SDRAM
Power	Power adapter
Power consumption	Max. 7W
Environment	Operating Temperature
Humidity	5%-90% RH
Physical Characteristics	Dimensions (LxWxH) (mm)
Net Weight	0.6 Kg
LCD	Size
Resolution	WQVGA
Brightness (cd/m2)	500
Viewing Angle (H-V)	140° / 120°
Touch	Touch Screen
I/O Interface	I/O Interface
1 x WIFI(802.11a/b/g/n)	
1 x Power In(terminal block DC input)	
1 x MiniSD Slot	
1 x LAN(10/100Mbps)	
6 x GPIO	
1 x CAN-bus	
2 x Speaker(1W)	
1 x USB 1.1	
1 x RS-422/485	

Ordering Information

IOVU-430S-CE6/ST/-R11	RISC PANEL PC, 4.3" LCD,ARM S3C2416X40-Y640 400MHz CPU, 128MB SDRAM,WIN CE6.0,RoHS
IOVU-430S-CE6/ST/WL/-R11	RISC PANEL PC, 4.3" LCD,ARM S3C2416X40-Y640 400MHz CPU,128MB SDRAM, BUILT-IN WIFI, WIN CE6.0,RoHS