

IOVU-751R

7" TFT WVGA LCD with resistive touchscreen



Features

- » 7" TFT WVGA LCD with resistive touchscreen
- » Alchemy™ AU1250 500 MHz CPU
- » Powered by Windows® CE 5.0
- » Built-in Ethernet LAN
- » Built-in RS-232/422/485 Port
- » Supports Power over Ethernet (PoE)
- » Multimedia support for MPEG 1/2/4 and WMV9

Specifications

Environment	
Operating Temperature	-20°C~60°C
LCD	
Brightness (cd/m2)	500
Resolution	WVGA
Size	7"
Viewing Angle (H-V)	140° / 100°
Physical Characteristics	
Dimensions (LxWxH) (mm)	226 x 140 x 41
Net Weight	0.8 Kg
Power	
Power adapter	9-30V DC input
Power consumption	Max. 14W
System	
CPU	Alchemy™ AU1250 500 MHz
Memory Ext.	256 MB DDR2
On-board Memory	2MB
Touch	
Touch Screen	Resistive Type
I/O Interface	
I/O Interface	2 x Speaker(1.5W)
	1 x Reset Button
	1 x RS-422/485
	1 x RS-232
	1 x Power Switch
	12 x Power In(jack/terminal block DC input)
	2 x LAN(10/100Mbps)
	2 x USB 2.0

Ordering Information

IOVU-751R-CE5/-R10

E206,RISC LCD PC 8.4"以下,7" RMI ALCHEMY AU1250 500MHZ PANEL PC,WITH POE
FUNCTION,WIN CE5.0 OS,RoHS